Magruder 210511 Safety Data Sheet

SECTION 1. IDENTIFICATION

Product Identifier Gypsum Products

Product List Gypsum Rock

Ground Gypsum Granular Gypsum

Recommended Use Agriculture, Portland Cement Rock, Industrial plaster, joint system and wall

board products.

Manufacturer/Importer/Supplier Distributor Information
Company Name Gypsum Resources Materials LLC

Address 8360 NV Hwy 159

Blue Diamond, NV 89004

Telephone E-mail

Emergency Phone Number

SECTION 2. HAZARDS IDENTIFICATION

Physical Hazards Not Classified

Health HazardsAcute toxicity, oralCategory 4Eye IrritationCategory 2B

Category 2B
Carcinogenicity
Category 1A
Specific target organ toxicity, repeated
Category 1 (lung)

Exposure

Environmental Hazards Not Classified. **OSHA Defined Hazards** Not Classified.

Label Elements



Signal Word Danger

Hazard Statement Harmful if swallowed. Causes eye irritation. May cause cancer. Causes damage

to organs (lung) through prolonged or repeated exposure.

Precautionary

Gypsum SDS Page 1 of 12 Preparation Date: 2019-9-10

Statement Prevention Obtain special instructions before use. Do not handle until all safety precautions

have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Call a poison center/doctor if you feel unwell. If in

eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention. Specific treatment (see section 4 on the SDS).

Storage

Disposal Store away from incompatible materials (see section 10 of the SDS). Protect

from moisture. Dispose of contents/container in accordance with applicable

regulations.

Hazard(s) not Otherwise

Classified (HNOC) None known.

Supplemental

Information None.

SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixtures

Chemical Name	Common name and synonyms	CAS number	%
GYPSUM (CALCIUM SULFATE)		10101-41-4	≤100
CRYSTALLINE SILICA (QUARTZ)		14808-60-7	0 -1

The specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition

Comments Gypsum (calcium sulfate) contains naturally occurring crystalline silica

(quartz) which is listed as a lung carcinogen. See Section 8 for exposure

intormation.

SECTION 4. FIRST AID MEASURES

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin Contact For skin contact, wash immediately with soap and water. Get medical attention

if irritation develops and persists.

Eye Contact Do not rub eyes. Immediately flush eyes with plenty of water for at least 15

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get

medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting without advice from poison control

center. If vomiting occurs, keep head low so stomach content doesn't get into

the lungs. Get medical advice/attention if you feel unwell.

Most Important Symptoms/effect, Acute and delayed

Causes eye irritation. Exposed individuals may experience eye tearing, redness,

and discomfort. Skin contact during hardening (rehydration) may slowly develop sufficient heat that may cause severe burns possibly resulting in permanent injury. Do not allow product to harden around any body part or allow

continuous, prolonged contact with skin. Handling can cause dry skin. Coughing.

Discomfort in the chest. Shortness of breath. Prolonged exposure may cause

chronic effects

Indication of Immediate medical Attention and Special treatment Needed

Provide general supportive measures and trat symptomatically. Keep victim

warm. Keep victim under observation. Symptoms may be delayed.

General

Information IF exposed or concerned: Get medical advice/attention. Ensure that medical

personnel are aware of material(s) involved, and take precautions to protect

themselves. Show this safety data sheet to the doctor in attendance.

SECTION 5. FIREFIGHTING MEASURES

Suitable

Extinguishing media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable

Extinguishing media

None known.

Specific hazards
Arising from the

Ansing from the

Chemical During fire, gases hazardous to health may be formed.

Spicial protective Equipment and Precautions for

Firefighters Self-contained breathing apparatus and full protective clothing must be worn in

case of fire.

Fire fighting Equipment/

Instructions Firefighters should wear full protective clothing including self contained

breathing apparatus. Use water spray to cool unopened containers.

Gypsum SDS Page 3 of 12 Preparation Date: 2019-9-10

Specific methods Use standard firefighting procedures and consider the hazards of other involved

materials.

General fire hazards No unusual fire or explosion hazards noted.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, Protective equipment And emergency Procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and Materials for Containment and Cleaning up Sweep up or gather material and place in appropriate container for disposal. Minimize dust generation and accumulation. Is sweeping of a contaminated area is necessary use a dust suppressant agent which does not react with the product. Contain the spill, then place in a suitable container. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewer, basements or confined areas.

Environmental Precautions

Keep out of drains, sewers, ditches, and waterways.

SECTION 7. HANDLING AND STORAGE

Precautions for safe Handling

Obtain special instructions before use. Do nt handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe Storage, including any Incompatibilities

Store in a dry place. Sote in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS). Keep awy from food, drink, and animal feedingstuffs.

Gypsum SDS Page 4 of 12 Preparation Date: 2019-9-10

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational

Exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
CRYSTALLINE SILICA	PEL	0.05 mg/m3	
(QUARTZ) (CAS			
14808-60-7)			
GYPSUM (CALCIUM	PEL	5 mg/m3	Respirable fraction.
SULFATE) (CAS			
10101-41-4)		15 MG/M3	Total Dust.

US ACGIH Threshold Limit Values: Time Weighted Average (TWA: mg/m3, non-standard units

Components	Туре	Value	Form
CRYSTALLINE SILICA	TWA	0.025 mg/m3	Respirable fraction.
(QUARTZ) (CAS			
14808-60-7)			
GYPSUM (CALCIUM	TWA	10 mg/m3	Inhalable fraction.
SULFATE) (CAS			
10101-41-4)			

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	Form
CRYSTALLINE SILICA	TWA	0.05 mg/m3	Respirable dust.
(QUARTZ) (CAS			
14808-60-7)			
GYPSUM (CALCIUM	TWA	5 mg/m3	Respirable.
SULFATE) (CAS			
10101-41-4)			
·		10 mg/m3	Total

Biological limit

Values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational exposure to nuisance dust (total and repirable) and respirable

crystalline silica should be monitored and controlled.

Appropriate

Engineering Controls When using product, provide local and general exhaust ventilation to keep

airborne dust concentrations below exposure limits. Use wet methods, if

appropriate, to reduce the generation of dust.

Individual protection measures, such as personal protective equipment

Eye/face

Protection Wear safety glasses with side shields (or goggles). Ensure compliance wit OSHA's

PPE Standard (29 CFR 1910.132 and .133) for eye and face protection. Eye wash

fountain is recommended.

Skin Protection

Hand Protection Wear appropriate chemical resistant gloves.

Gypsum SDS Page 5 of 12 Preparation Date: 2019-9-10

Other Impervious protective clothing and gloves recommended to prevent drying or

irritation of skin. Ensure compliance with OSHA's PPE Standard (29 CFR 1910.132 (general) and 138 (hand protection)). Safety shower/eye wash fountain is recommended in the workplace area (29 CFR 1910.151 (c)).

Respiratory

Protection A NIOSH approved dust mask or filtering facepiece is recommended in poorly

ventilated areas or when permissible exposure limits may be exceeded. Respirators should be selected by and used under the direction of a trained health and safety professiona following requirements found in OSHA's respirator standard (29 CFR 1910.134) and ANSI's standard for respiratory

protection (Z88.2).

Thermal

Hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene

Considerations Observe any medical surveillance requirements. Keep away from food and

drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state Solid. **Form** Powder.

Color Light grey to white

Odor Low Odor
Odor Threshold Not available

pH 6-8

Melting Point/

Freezing Point 2642°F (1450 °C) estimated

Initil boiling point

And boiling rangeNot ApplicableFlash pointNot ApplicableEvaporation rateNot ApplicableFlammability (solid)Not Applicable

Upper/lower flammability or explosive limits

Flammablility limit-

Lower(%) Not Applicable

Flammablility limit-

Upper(%) Not Applicable

Explosive limit-

Lower (%) Not Applicable

Explosive limit-

Upper (%) Not Applicable
Vapor pressure Not Applicable

Vapor densityNot ApplicableRelative density2.3 g/cm3

Solubility (ies)

Solubility (water) 0.23% @22°C **Partition coefficient** Not Available

(n-octanol/water)

Auto-ignition temperatureNot ApplicableDecomposition temperatureNot ApplicableViscosityNot Available

Other information

Explosive propertiesNot ExplosiveFlash point classNot flammableOxidizing propertiesNot Oxidizing.

Specific gravity 2.3

SECTION 10. STABILITY AND REACTIVITY

Reactivity The product is stable and non-reactive under normal conditions of use, storage

and transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous

Reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed

air). Contact with incompatible materials. Exposure to moisture.

Incompatible

Materials Acids

Hazardous Decomposition

Products May include and are not limited to : calcium oxide and sulfur dioxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by

inhalation. Dust may irritate respiratory system.

Skin contact Dust or powder may irritate the skin.

Eye contact Causes eye irritation. **Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological

characteristics Causes eye irritation. Exposed individuals may experience eye tearing,

redness, and discomfort. Dusts may irritate the respiratory tract, skin and

eyes. Coughing. Discomfort in the chest. Shortness of breath.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Product Species Test Results

Uncalcined Gypsum Products

Acute Oral

LD50 Rat 1581 mg/kg estimated

Components Species Test Results

GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4)

Acute Oral

LD50 Rat >1581 mg/kg

* Estimates for product may be based on additional component data not shown **rrosion/irritation** Prolonged skin contact may cause temporary irritation.

Skin corrosion/irritation Serious eye damage/eye

Carcinogenicity

Irritation Causes eye irritation.

Respiratory or skin

Sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization. **Germ cell mutagenicity** No data available to indicate product or any components

present at greater than 0.1% are mutagenic or genotoxic. Exposure to respirable crystalline silica in the form of

quartz or cristobalite from occupational sources is listed by IARC and NTP as a lung carcinogen. Prolonged exposure to respirable crystalline silica has been known to cause silicosis, a lung disease, which may be disabling. While there may be a factor of individual susceptibility to a given exposure to a respirable silica dust, the risk of contracting silicosis and the severity of the disease is clearly related to

the amount of respirable crystalline silica exposure and the

length of time (usually years) of exposure

IARC Monographs. Overall Evaluation of Carcinogenicity

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Known To Be Human

Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or

developmental effects.

Specific target organ toxicity -

single exposure Not classified.

Specific target organ toxicity – Causes damage to organs (lung) through prolonged or

repeated exposure.

repeated exposure

Gypsum SDS Page 8 of 12 Preparation Date: 2019-9-10

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may

cause chronic effects.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity The product is not classified as environmentally hazardous.

However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

Components Species Test Results

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

Aquatic

Acute

Fish LC50 Zebra danio (Danio rerio) > 10000 mg/l, 96Hours OECD SIDS GYPSUM (CALCIUM SULFATE) (CAS 10101-41-4)

Aquatic

Fish LC50 Fish 2980 mg/l, 96 Hours

Persistence and degradability No data is available

Bioaccumulative potential No data available. on the degradability of

Mobility in soil No data available. 1

Other adverse effects No other adverse environmental effects (e.g. ozone

depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are

expected from this component.

Gypsum SDS Page 9 of 12 Preparation Date: 2019-9-10

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal Instructions Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user,

the producer and the waste disposal company.

Waste from residues/

Unused products Dispose of in accordance with local regulations. Empty containers

or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated Packaging Since emptied containers may retain product residue, follow label

warnings even after container is emptied. Empty containers should

be taken to an approved waste handling site for recycling or

disposal.

SECTION 14. TRANSPORT INFORMATION

DOT

Not regulated as dangerous goods.

Transport in bulk according

Not applicable.

to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15. REGULATORY INFORMATION

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA

Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories Immediate Hazard - Yes

Delayed Hazard - Yes

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

Gypsum SDS Page 10 of 12 Preparation Date: 2019-9-10

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7)

US. California Proposition 65

WARNING: This product can expose you to chemicals including Crystalline Silica (Quartz), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance CRYSTALLINE SILICA (QUARTZ) (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region Inventory name

Canada Domestic Substances List (DSL)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Gypsum SDS Page 11 of 12 Preparation Date: 2019-9-10

SECTION 16. OTHER INFORMATION

Issue date September-10-2019

Version # 01

HMIS® ratings Health: 2

Flammability: 0 Instability: 0

Disclaimer This SDS is intended to quickly provide useful information to the user(s)

of this material or product. It is not intended to serve as a comprehensive discussion of all possible risks or hazards, and it assumes a reasonable use of the product. The information contained in this SDS is believed to be accurate as of the date of preparation of this SDS and has been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. The user or handler (or their employer) should consider the specific conditions in which this material will be used, handled, or stored and determine what specific safety or other precautions are required. Employers should ensure that their employees, agents, contractors, and customers who will use the product receive adequate warnings and safe handling procedures, including a current SDS. Product users or handlers (or their employer) who are unsure of what specific precautions are required should consult their employer, product supplier, or safety or health professionals before handling or working with this product. Please notify us immediately if you believe this SDS or other safety and health information about this product is inaccurate or incomplete.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Gypsum SDS Page 12 of 12 Preparation Date: 2019-9-10