Magruder 250631

32-0-0 UAN Solution

Results due July 15, 2025

Total Nitrogen (N)32.0%

also analyze for: Ammoniacal Nitrogen Nitrate Nitrogen Biuret Nitrogen Urea Nitrogen

The units above are those required for reporting data from this Magruder sample.

They may not be the units required on a commercial fertilizer label.

Note: This Magruder Check Sample material is not to be used in the manufacture of products nor applied to any crops or for other fertilizer uses. It is intended for analytical testing purposes only.

SDS for this product can be found at:

https://www.magruderchecksample.org/SDS/250631GuarSDS.pdf

SDS for Magruder 250631

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: Urea Ammonium Nitrate Solution - 28%, 30%, 32% N (UAN)

CAS No: 15978-77-5 REACH No.: N/A - mixture

Synonyms: UAN (28, 30, and 32% N), Liquid nitrogen fertilizer

STCC: 2871313

1.2. Intended Use of the Product Uses of the substance/mixture: Fertilizer Uses advised against: Consumer use

1.3. Name, Address, and Telephone of the Responsible Party

Company **CF Industries** 4 Parkway North, Suite 400

Deerfield, Illinois 60015-2590

847-405-2400

www.cfindustries.com

Emergency Telephone Number

Emergency Number: 800-424-9300

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Accident, call CHEMTREC - Day or Night

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture 2.1.

Classification (GHS-US)

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

Label Elements 2.2.

GHS-US Labeling

Hazard Pictograms (GHS-US)



: Warning Signal Word (GHS-US)

: H319 - Causes serious eye irritation. **Hazard Statements (GHS-US)**

Precautionary Statements (GHS-US) P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

P280 - Wear protective gloves, protective clothing, and eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other Hazards

No additional information available

Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Name	Product Identifier	REACH	% (w/w)	Classification (GHS-US)
		Registration No.		
Urea Ammonium Nitrate	(CAS No) 15978-77-5	N/A mixture	100	Eye Irrit. 2A, H319
Contains	Product Identifier		% (w/w)	Classification (GHS-US)
Ammonium nitrate	(CAS No) 6484-52-2	01-21 1949 0981 -	35.7 - 48	Ox. Sol. 3, H272
		27-0111		Eye Irrit. 2A, H319
Urea	(CAS No) 57-13-6	01-21 1946 3277 -	28.5 - 38	Not classified
		33-0135		
Water	(CAS No) 7732-18-5	N/A	19.4 -	Not classified
			31.1	

Full text of H-phrases: see section 16

3.2. Mixture

Not applicable

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Call a POISON CENTER/doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

General: Causes eye irritation.

Inhalation: May cause irritation to the respiratory tract.

Skin Contact: May cause skin irritation.

Eye Contact: Causes eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision. **Ingestion:** Ammonium Nitrate: Ingestion may cause methemoglobinemia. Intial manifestation of methemoglobinemia is cyanosis, characterized by navy lips, tongue and mucous membranes, with skin color being slate grey. Further manifestation is characterized by headache, weakness, dyspnea, dizziness, stupor, respiratory distress and death due to anoxia. If ingested, nitrates may be reduced to nitrites by bacteria in the digestive tract. Signs and symptoms of nitrite poisoning include methemoglobinemia, nausea, dizziness, increased heart rate, hypotension, fainting and possibly shock.

Chronic Symptoms: Overexposure to this material may result in methemoglobinemia.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. Hot Ammonium Nitrate burns skin, allowing rapid absorption of Ammonium Nitrate through the skin and toxic effects can occur quite rapidly. Causes methemoglobinemia – emergency response should treat appropriately, such as by intravenous administration of methylene blue.

ECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Contains substances that are oxidizers when in solid form. May cause fire or explosion if allowed to dry.

Explosion Hazard: May be explosive in contact with flammable or organic substances and confinement during fire.

Reactivity: Accelerates the rate of burning materials. Oxidizer if allowed to dry.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions closed containers may rupture or explode.

Firefighting Instructions: Do not allow product to evaporate to dryness. For fires beyond the incipient stage, emergency responders in the immediate hazard area should wear bunker gear. Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done with minimal risk. Move undamaged containers from immediate hazard area if it can be done with minimal risk. Water spray may be useful in minimizing or dispersing vapors. Cool equipment exposed to fire with water, if it can be done with minimal risk.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. **Hazardous Combustion Products:** Nitrogen oxides. Ammonia. Toxic vapors. Carbon oxides (CO, CO2).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray.

6.1.1. For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE). **Emergency Procedures:** Evacuate unnecessary personnel. Eliminate ignition sources.

6.1.2. For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection. **Emergency Procedures:** Stop leak if safe to do so. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Contact competent authorities after a spill.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Absorb and/or contain spill with inert material, then place in suitable container. Do not take up in combustible material such as: saw dust or cellulosic material. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Additional Hazards When Processed: When the water in UAN evaporates, residue may include solid ammonium nitrate and urea. When sensitized or during decomposition, solid ammonium nitrate may become unstable and/or explosive. UAN pumps operated with blocked discharge have been known to detonate. Smothering, contact with organic material, or combustible material may cause an explosive situation. Thoroughly wash out pipes, tanks, or valves before welding or burning. Residual solidified ammonium nitrate may explode under high temperatures and confinement. Heating above 140°F will promote hydrolysis. Extreme cold (< 32 °F) may cause crystallization of the product. Do not allow liquid to evaporate, as solid ammonium nitrate residue can explode. Precautions for Safe Handling: Use only outdoors or in a well-ventilated area. Avoid all eye and skin contact, and do not breathe vapor and mist. Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash contaminated clothing before reuse.

7.2.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Ventilate confined spaces before entering. Proper grounding procedures to avoid static electricity should be followed. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool, and well-ventilated place. Keep in fireproof place. Store locked up. Store away from oxidizers, combustible materials, and all ignition sources. Protect container(s) against corrosion, physical damage, and extreme temperatures. Detached outside storage is preferable. May be corrosive to some metals.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Chlorine. Hypochlorites. Metallic powders. Combustible materials. Chromates. Zinc. Copper and its alloys. Chlorates.

7.3. Specific End Use(s)

Fertilizer

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government.

8.2. Exposure Controls

Appropriate Engineering Controls: Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use explosion-proof equipment. Ensure all national/local regulations are observed. Provide sufficient ventilation to keep ammonia vapors below the permissible exposure limit

Personal Protective Equipment: Gloves. Protective goggles. Insufficient ventilation: wear respiratory protection. Protective clothing.









Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Chemical resistant suit. Rubber apron, boots.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Other Information: When using, do not eat, drink, or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State : Liquid Colorless liquid Little or no detectable ammonia odor Not Appearance : available 6.5 - 7.8 Not available 0°F (-18°C) for 28%N; 16°F (-9°C) for

Odor : 30%N; 32°F (0°C) for 32%N (salt out

Odor Threshold : temperature)
pH : Not available

Evaporation Rate : > 100 °C (> 212 °F) **Melting Point** : Not available

Freezing Point : Not available

Poiling Point : Not available

Boiling PointNot availableFlash PointNot availableAuto-ignition TemperatureNot available

Decomposition Temperature : 0.11 - 0.06 psia (28%, 32% respectively) @60°F (15.6°C) due to water

Flammability (solid, gas) component

Lower Flammable Limit

Upper Flammable Limit

Not available 10.67 lbs/gal (28%N); 10.86 lbs/gal (30%N); 11.08 lbs/gal (32% N) 1.281 (28%N); 1.304 (30%N); 1.330 (32%N) @60°F (16°C)

Miscible Urea: -1.59, Ammonium Nitrate: -3.1 3.6 cP (28%N); 6.1 cP

Vapor Pressure : (32%N) @40°F (4.4°C) Not expected to present an explosion hazard due to mechanical impact. Not expected to present an explosion hazard

Relative Vapor Density at 20 °C : due to static discharge.

Relative Density : Specific Gravity :

Solubility : Partition Coefficient: N-Octanol/Water :

Viscosity

Explosion Data – Sensitivity to Mechanical Impact: Explosion Data – Sensitivity to Static Discharge:

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

Accelerates the rate of burning materials. Oxidizer if allowed to dry.

10.2. Chemical Stability

Stable.

10.3. **Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

Conditions to Avoid 10.4.

Extremely high or low temperatures. Open flame. Heat. Sparks. High pressures- explodes if heated under confinement. Do not allow product to dry out. When the water in UAN evaporates, residue may include solid ammonium nitrate and urea. When sensitized or during decomposition, solid ammonium nitrate may become unstable and/or explosive. UAN pumps operated with blocked discharge have been known to detonate.

10.5. Incompatible Materials

Strong acids. UAN will form urea nitrate when mixed with nitric acid at low pH. Urea nitrate may become unstable and/or explosive under certain conditions. Strong bases, Strong oxidizers, Chlorine, Hypochlorites, UAN will form nitrogen trichloride, which may be explosive, when mixed with chlorine and hypochlorite. Metallic powders. Combustible materials. Chromates. Zinc. Copper and its alloys. Chlorates.

10.6. Hazardous Decomposition Products

Nitrogen oxides. Ammonia. Carbon oxides (CO, CO2). When the water in UAN evaporates, residue may include solid ammonium nitrate and urea. When sensitized or during decomposition, solid ammonium nitrate may become unstable and/or explosive. UAN pumps operated with blocked discharge have been known to detonate.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available Skin Corrosion/Irritation: Not classified

pH: 6.5 - 7.8

Serious Eye Damage/Irritation: Causes serious eye irritation.

pH: 6.5 - 7.8

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause irritation to the respiratory tract.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing,

Symptoms/Injuries After Ingestion: Ammonium Nitrate: Ingestion may cause methemoglobinemia. Intial manifestation of methemoglobinemia is cyanosis, characterized by navy lips, tongue and mucous membranes, with skin color being slate grey. Further manifestation is characterized by headache, weakness, dyspnea, dizziness, stupor, respiratory distress and death due to anoxia. If ingested, nitrates may be reduced to nitrites by bacteria in the digestive tract. Signs and symptoms of nitrite poisoning include methemoglobinemia, nausea, dizziness, increased heart rate, hypotension, fainting and possibly shock.

Chronic Symptoms: Overexposure to this material may result in methemoglobinemia.

11.2. Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Water (7732-18-5)	
LD50 Oral Rat	> 90000 mg/kg
Urea (57-13-6)	
LD50 Oral Rat	8471 mg/kg

Ammonium nitrate (6484-52-2)	
LD50 Oral Rat	2217 mg/kg
LC50 Inhalation Rat	> 88.8 mg/l/4h

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No additional information available

Urea (57-13-6)	
LC50 Fish 1	16200 - 18300 mg/l (Exposure time: 96 h - Species: Poecilia reticulata)
EC50 Daphnia 1	3910 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

12.2. Persistence and Degradability

Urea Ammonium Nitrate Solution- 28%, 30%, 32% N (UAN) (15978-77-5)	
Persistence and Degradability	Not established.

12.3. Bioaccumulative Potential

Urea Ammonium Nitrate Solution- 28%, 30%, 32% N (UAN) (15978-77-5)		
Log Pow	-1.14	
Bioaccumulative Potential	Not established.	
Urea (57-13-6)		
BCF Fish 1	< 10	
Log Pow	-1.59 (at 25 °C)	
Ammonium nitrate (6484-52-2)		
BCF Fish 1	(no bioaccumulation expected)	
Log Pow	-3.1 (at 25 °C)	

12.4. Mobility in Soil

Not available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Sewage Disposal Recommendations: Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT

Not regulated for transport

14.2. In Accordance with IMDG

Not regulated for transport

14.3. In Accordance with IATA

Not regulated for transport

14.4. In Accordance with TDG

Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

Urea Ammonium Nitrate Solution - 28% , 30%, 32% N (UAN) (15978-77-5)		
SARA Section 311/312 Hazard Classes Immediate (acute) health hazard		
Water (7732-18-5)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Urea (57-13-6)		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		

Ammonium nitrate (6484-52-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. US State Regulations

Urea (57-13-6)

- U.S. Minnesota Hazardous Substance List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

Ammonium nitrate (6484-52-2)

- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)
- U.S. Delaware Accidental Release Prevention Regulations Sufficient Quantities
- U.S. Delaware Pollutant Discharge Requirements Reportable Quantities
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- RTK U.S. Massachusetts Right To Know List
- RTK U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List
- RTK U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- RTK U.S. Pennsylvania RTK (Right to Know) List
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term

15.3. Canadian Regulations

Urea Ammonium Nitrate Solution- 28%, 30%, 32% N (UAN) (15978-77-5)

WHMIS Classification

IIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification Uncontrolled product according to WHMIS classification criteria		
Urea (57-13-6)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	

Ammonium nitrate (6484-52-2)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification Class C - Oxidizing Material

Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 29 September 2018

Revision Comments : This document has undergone extensive revisions and should be reviewed in its entirety.

GHS Full Text Phrases:

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Ox. Sol. 3	Oxidizing solids Category 3 May intensify fire;
H272 H319	oxidizer Causes serious eye irritation

NFPA Rating

Health Hazard : 2 - Intense or continued exposure could cause temporary

incapacitation or possible residual injury unless prompt

medical attention is given.

Fire Hazard : 0 - Materials that will not burn.

Reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.

HMIS III Rating

Health : 2 Moderate Hazard – Temporary or minor injury may occur

Flammability : 0 Minimal Hazard Physical : 0 Minimal Hazard

Party Responsible for the Preparation of This Document

CF Industries, Corporate EHS Department, 847-405-2400

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

CF believes the information contained herein is accurate; however, CF makes no guarantees or warranties with respect to such accuracy and assumes no liability in connection with the use of the information contained herein by any party. The provision of the information contained herein by CF is not intended to be and should not be construed as legal advice or as ensuring compliance by other parties. Judgments as to the suitability of the information contained herein for the party's own use or purposes are solely the responsibility of that party. Any party handling, transferring, transporting, storing, applying or otherwise using this product should review thoroughly all applicable laws, rules, regulations, standards and good engineering practices. Such thorough review should occur before the party handles, transfers, transports, stores, applies or otherwise uses this product.

